

# HOLSAG CANADA

Seating Manufacturer

## Specifications: Bubba Barstool

**Description:** The Bubba joins the Bulldog family as a “Beefed Up” version of our popular barstool. The side rails are extra thick for added support. Three kick plates are standard. The back slats are raised from the seat to allow for easy cleaning. Upholstered seats as well as solid wood seats are available. The wood seats are sculpted at the factory to ensure a comfortable sitting position.

### Dimensions: Barstool

Overall Height	46.75”	118.75 cm
Overall Depth	19.00”	48.26 cm
Seat Height	30.00”	76.20 cm
Seat Depth	16.50”	41.91 cm
Seat Width	17.00”	43.18 cm
Barstool Weight	22 lbs	10 kg
Carton Weight		
with 1 stool	32 lbs	14.5 kg
Carton Size for 1 Barstool		
	18.5” x 20” x 48”	
	46.3 cm x 50.8 cm x 121.8 cm	
Volume		10.3 cubic feet

*Note:* The barstool is available in custom seat heights ranging from 24” (61 cm) to 30” (76 cm).

**Standard Barstool Kick plates** are brass. Chrome or black kick plates are available upon request at the same price.

**Fabric for upholstered seats:**  
COM (Customer’s Own Material)  
fabric required:  
.35 yard (.33 m) per stool

*Note:* Fabric amount is estimated on 54” (137 cm) wide material. The actual amount required may vary depending on special pattern matching and the width of the material.

**Cushion Foam:** High density foam on seat

**Wood:**  
*Species:* 100% Solid European Beech Hardwood

**Construction:**  
*Joints:* Mortise and tenon.  
Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

**Stain Colours:**  
A wide range of standard stain colours is available as well as custom colour matching. (A surcharge will apply to custom colours.)

### 9-Step Finishing Process:

1. The bare wood of the assembled product is thoroughly sanded using 100 grit paper.
2. One coat of stain is sprayed onto the entire product – including the underside of the seat.
3. The stain is hand wiped to ensure an even colour and maximum penetration into the wood.
4. The product is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 280 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



*Note:* Specifications are subject to change without notice.



## Holsag Canada

164 Needham Street  
Lindsay, Ontario Canada  
K9V 5R7  
(705) 878-1970  
(888) 745-0721 (U.S. & Canada)  
Fax: (705) 878-1864 [www.holsag.com](http://www.holsag.com)