

HOLSAG CANADA

Seating Manufacturer

Specifications: Henry Chair and Barstool

Description: The Henry chair and barstool are styled to the classic “Library” design. Details such as the elegant, slightly fanned back with six slats and decorative brackets on the edge of the seat give this chair a timeless design. Upholstered seats as well as solid wood seats are available. The wood seats are sculpted at the factory to ensure a comfortable sitting position.

Dimensions: Chair

Overall Height	34.25”	87.00 cm
Overall Depth	20.75”	52.71 cm
Seat Height	18.00”	45.72 cm
Seat Depth	16.25”	41.28 cm
Seat Width	18.25”	46.36 cm
Chair Weight	17 lbs	7.7 kg
Carton Weight		
with 1 chair	27 lbs	12 kg
with 2 chairs	44 lbs	20 kg
Carton Size for 1 Chair		
	19.5” x 22” x 37.5”	
	49.5 cm x 56 cm x 95.25 cm	
Carton Volume for 1 Chair		
	9.3 cubic feet	
<i>Note: Packing of chairs is based on the shipping method.</i>		

Dimensions: Barstool

Overall Height	43.00”	109.22 cm
Overall Depth	19.25”	48.90 cm
Seat Height	30.00”	76.20 cm
Seat Depth	16.25”	41.28 cm
Seat Width	18.25”	46.36 cm
Barstool Weight	17 lbs	7.7 kg
Carton Weight		
with 1 stool	27 lbs	12 kg
Carton Size for 1 stool		
	19.75” x 20” x 44.5”	
	50 cm x 51 cm x 113 cm	
Carton Volume for 1 stool		
	10 cubic feet	

Note: The barstool is available in custom seat heights ranging from 24” (61 cm) to 30” (76 cm).

Standard Barstool Kick plates are brass. Chrome or black kick plates are available upon request at the same price.

Fabric for upholstered seats: COM (Customer’s Own Material) fabric required (chair and barstool): .35 yd (.33 m)

Note: This is the estimated amount based on 54” (137 cm) wide material. The actual amount required may vary depending on special pattern matching and the width of the material.

Cushion Foam: High density foam on seat

Wood:
Species: 100% Solid European Beech Hardwood


Construction:
Joints: Mortise and tenon. Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

Stain Colors:
A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

9-Step Finishing Process:

1. The bare wood of the assembled chair is thoroughly sanded using 100 grit paper.
2. One coat of stain is sprayed onto the entire chair – including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.

4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 280 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



Note: Specifications are subject to change without notice.



Holsag Canada

164 Needham Street
Lindsay, Ontario Canada
K9V 5R7
(705) 878-1970
(888) 745-0721 (U.S. & Canada)
Fax: (705) 878-1864

www.holsag.com